

CURIX 60 PROCESSOR

High-quality images with
table-top processor



Maximum performance on minimum footprint

The Curix 60 is a table-top processor equipped with highly performant technology. It can be easily fitted into a small space, still guaranteeing maximum image quality. The Curix 60 is ideal for low-volume radiology and provides consistent, high-quality processing of film with a maximum width of 36 cm.

Furthermore, the Curix 60 may serve as an ideal back-up for your regular processor.

Superior performance

Thanks to the infrared dryer, superior drying performance is obtained together with low power consumption and a low noise level. To ensure consistent high-quality images, the bath temperature is controlled electronically.

Compact and time-saving

Due to the clever location of the replenisher tanks, the position of the film delivery slot and the boomerang system, which brings the processed film on top of the processor, its floor

space is minimal and access is easy. The exclusive Curix 60 light-tight cover design allows you to leave the darkroom after approx. 15 seconds. You don't need to wait until the film completely entered the processor.

Kind to your working environment

When you open the Curix 60 processor, you will notice that both the chemical tanks and the rollers are covered. Your working environment will not be disturbed by chemical fumes any more.

Optimum replenishment

On the whole, the flow of replenishment is controlled by scanning the film surface. When the Curix 60 is used at irregular intervals, half the contents of the developing tray can be replaced by simply pressing the 'Optimising key', i.e. the black key in the middle.

Curix 60

Technical data

Dimensions (l x w x h) with feedtable		Film sizes	Warming-up time
94 x 65 x 37 cm (37 x 25.5 x 14.5 in)		Min. size: 10 x 10 cm (diagonally)	7 min
		Max. width: 36 cm	
Weight		No Roll film	Noise level
Empty: 62 kg (136 lbs)			Max 55 dB (A)
With replenisher bottles: 72 kg (158 lbs)		Drying system	(ISO standard 7779)
		Infrared	
Tank capacity		Standard equipment	Design features
Developer tank:	0.9 l (0.2 gal)	Processor + set of 3 replenisher bottles	Compliance with EN61000-3-2 and
Fixer tank:	0.9 l		EN 61000-3-3
Wash tank:	0.9 l		
Replenisher bottles:	2.5 l (0.7 gal)	Accessories	Power supply
		Water supply connection	200-240 V AC 50/60 Hz
Capacity		Light-tight cover	Max. consumption: 1700 W
60 films/hour		Processor stand	Continuous consumption: 500 W
(24 x 30 cm)		Set of three replenisher bottles of 2.5 l	In stand-by: 180W
		(3 x 0.66 gal)	
Processing cycle		External replenishment kit	Safety
3 min		Automatic stand-by mode	This processor complies with the VDE, UL and
			CSA safety regulations and with the VDE
Film transport speed		'Optimising key' for replenishment	regulations on radio interference suppression.
28 cm/min			The non-return water connection complies
			with the DIN standard for connection to
			drinking water systems. The unit is supplied
			with the TÜV and CE label for medical device.

Not all options/products mentioned in this data sheet are available in all countries. In case of doubt, please contact your Agfa Sales Organisation.

The data in this publication are for illustration purposes only and do not necessarily represent standards or specifications which must be met by Agfa. Characteristics of the products described in this publication can be changed at any time without notice.

Curix is a trademark of Agfa-Gevaert N.V., Belgium.
Agfa and the Agfa-Rhombus are trademarks of Agfa-Gevaert AG, Germany.

Printed in Belgium
Published by Agfa-Gevaert N.V.,
B-2640 Mortsel-Belgium
NEKHL GB 00200105 V04